

BLOWER DC FANS

BNTA SERIES Ø100×25 mm

- * Material: Impeller: Plastic (UL 94V-0) & Frame: Diecast Aluminum
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 9 Blades
- * Rotational direction CW view from front face
- * Weight: 123g (4.34 OZ)



BLOWER DC FANS

BA SERIES Ø100×33 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 43 Blades
- * Rotational direction CCW view from front face
- * Weight: 180 g (6.35 OZ)



ASIA VITAL COMPONENTS CO., LTD. SixSigma														ASIA VITAL COMPONENTS CO., LTD. SixSigma													
MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L ₁₀ @40°C	MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L ₁₀ @40°C				
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m³/min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours	PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m³/min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
BNTA1025B85	-FG	8	48	36 to 56	0.42	20.16	6700	1.997	70.52	62.80	2.472	65.1	70000	BA10033B_12L	-FG/RD	8	12	7.0 to 13.8	0.38	4.56	2700	0.685	24.20	18.93	0.745	48.0	120000

